



## 主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN15 (1/2")	PN16 CL150	DA052	188	147			108	48	3
		SR075	216	184					4.4
	PN25/40 CL300	DA052	174	147			140	48	4
		DA063	190	168					4.6
		DA075	202	184					5.4
		DA083	212	204					6.1
		SR075	202	184					5.4
		SR092	222	262					7.7
		SR105	235	268					9.4
		SR125	257	301					12.6
	PN63/110 CL600	DA052	174	147			165	53	4.5
		DA063	190	168					5.1
		DA083	212	204					6.6
		DA092	222	262					8.2
		SR075	202	184					5.9
		SR083	212	204					6.6
		SR105	235	268					9.9
		SR125	257	301					13.1
SR140	274	390			18				

注：本表尺寸和重量不包含附件。

# 浮动球阀外形尺寸



## 主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN20 (3/4")	PN16 CL150	DA052	193	147			117	53	3.5
		SR075	221	184					4.9
	PN25/40 CL300	DA052	176	147			152	53	4.5
		DA063	192	168					5.1
		DA075	204	184					5.9
		DA083	214	204					6.6
		SR075	204	184					5.9
		SR083	214	204					6.6
		SR092	224	262					8.2
		SR105	237	268					9.9
	SR125	259	301			13.1			
	PN63/110 CL600	DA052	176	147			190	65	5.5
		DA063	192	168					6.1
		DA083	214	204					7.6
		DA092	224	262					9.2
		SR075	204	184					6.9
		SR083	214	204					7.6
		SR105	237	268					10.9
SR125		259	301			14.1			
SR140	276	390			19				
DN25 (1")	PN16 CL150	DA063	214	168			127	57	5.1
		DA075	226	184					5.9
		SR083	236	204					6.6
		SR092	246	262					8.2
		SR105	259	268					9.9
	PN25/40 CL300	DA063	199	168			165	57	7.1
		DA075	211	184					7.9
		DA083	221	204					8.6
		SR083	221	204					8.6
		SR092	231	262					10.2
		SR105	244	268					11.9
	SR125	266	301			15.1			
	PN63/110 CL600	DA052	183	147			216	63	7.5
		DA063	199	168					8.1
		DA083	221	204					9.6
		DA092	231	262					11.2
		SR083	221	204					9.6
		SR105	244	268					12.9
SR125		266	301			16.1			
SR140	283	390			21				

注：本表尺寸和重量不包含附件。



主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)	
DN32 (1-1/4")	PN16 CL150	DA075	235	184			140	70	6.9	
		DA083	245	204					7.6	
		SR092	255	262					9.2	
		SR125	290	301					14.1	
	PN25/40 CL300	DA075	235	184			178	70	8.9	
		DA083	245	204					9.6	
		DA092	255	262					11.2	
		SR092	255	262					11.2	
		SR105	268	268					12.9	
		SR125	287	301					16.1	
	PN63/110 CL600	SR140	307	390					21	
		DA075	232	184			229	78	9.9	
		DA083	242	204					10.6	
		DA092	252	262					12.2	
		DA105	265	268					13.9	
		DA125	287	301					17.1	
		SR105	265	268					13.9	
		SR125	287	301					17.1	
	SR140	304	390			22				
	DN40 (1-1/2")	PN16 CL150	SR160	329	458					31
			DA083	250	204			165	75	10.6
			DA092	260	262					12.2
			SR105	273	268					13.9
		SR140	312	390			22			
PN25/40 CL300		DA083	250	204			190	75	13.6	
		DA092	260	262					15.2	
		DA105	273	268					16.9	
		SR125	295	301					20.1	
		SR140	312	390					25	
PN63/110 CL600		DA083	250	204			241	85	16.6	
		DA092	260	262					18.2	
		DA105	273	268					19.9	
		DA125	295	301					23.1	
		DA140	312	390					28	
		SR125	295	301					23.1	
		SR140	312	390					28	
		SR160	337	458					37	
		SR190	380	525					48	

注：本表尺寸和重量不包含附件。

# 浮动球阀外形尺寸



## 主要外形尺寸及重量

公称口径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)	
DN50 (2")	PN16 CL150	DA092	287	262			178	83	16.2	
		DA105	300	268					17.9	
		SR125	322	301					21.1	
		SR140	339	390					26	
		AW13S	420		320	760			76	
	PN25/40 CL300	DA092	287	262			216	83	19.2	
		DA105	300	268					20.9	
		DA125	322	301					24.1	
		SR125	322	301					24.1	
		SR140	339	390					29	
		SR160	364	458					38	
	PN63/110 CL600	AW13S	420		320	760			79	
		DA092	294	262			292	98	27.2	
		DA105	3074	268					28.9	
		DA125	329	301					32.1	
		DA140	346	390					37	
		SR125	329	301					32.1	
		SR140	346	390					37	
		SR160	371	458					46	
	SR190	414	525			57				
	DN65 (2-1/2")	PN16 CL150	AW13S	427		320	760			87
			DA105	311	268			190	93	21.9
			DA125	333	301					25.1
			SR160	375	458					39
AW13S			431		320	760	80			
AW17S		525		368	862	135				
PN25/40 CL300		DA105	311	268			241	93	28.9	
		DA125	333	301					32.1	
		DA160	375	458					46	
		SR140	350	390					37	
		SR160	375	458					46	
		SR190	418	525					57	
		AW13S	431		320	760			87	
		AW17S	525		368	862			142	
PN63/110 CL600		DA105	331	268			330	110	41.9	
		DA125	353	301					45.1	
		DA160	395	458					59	
		SR160	395	458					59	
		SR190	438	525					70	
		SR210	463	532					90	
		AW13S	451		320	760			100	
		AW17S	545		368	862			155	

注：本表尺寸和重量不包含附件。





主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN80 (3")	PN16 CL150	DA125	355	301			203	100	33.1
		DA140	372	390					38
		SR160	397	458					47
		SR190	440	525					58
		AW13	453	640					88
		AW13S	453		320	760			88
		AW17S	547		368	862			143
		AW20S	590		510	1200			213
	PN25/40 CL300	DA125	355	301			282	100	42.1
		DA140	372	390					47
		DA160	397	458					56
		SR160	397	458					56
		SR190	440	525					67
		SR210	465	532					87
		AW13	453	640					97
		AW13S	453		320	760			97
		AW17S	547		368	862			152
		AW20S	590		510	1200			222
	PN63/110 CL600	DA125	377	301			356	110	56.1
		DA140	394	390					61
		DA160	419	458					70
		DA190	462	525					81
		SR210	487	532					101
		AW13	475	640					111
		AW13S	475		320	760			111
		AW17S	569		368	862			166
		AW20S	612		510	1200			236

注：本表尺寸和重量不包含附件。

# 浮动球阀外形尺寸



## 主要外形尺寸及重量

公称口径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN100 (4")	PN16 CL150	DA140	402	390			229	110	55
		DA160	327	458					64
		SR190	470	525					75
		SR210	495	532					95
		SR240	529	602					120
		AW13	483	640					105
		AW17S	577		368	862			160
		AW20S	620		510	1200			230
	PN25/40 CL300	DA160	327	458			305	118	74
		DA190	470	525					85
		SR190	470	525					85
		SR210	495	532					105
		SR240	529	602					130
		AW13	483	640					115
		AW17	577	736					170
		AW17S	577		368	862			170
	AW20S	620		510	1200	240			
	PN63/110 CL600	DA160	492	458			432	150	104
		DA190	535	525					115
		DA240	594	602					160
		SR210	560	532					135
		SR240	594	602					160
		AW13	548	640					145
		AW20	685	1020					270
		AW17S	642		368	862			200
		AW28S	825		690	1578			515

注：本表尺寸和重量不包含附件。



主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN125 (5")	PN16 CL150	DA160	454	458			356	125	74
		DA190	497	525					85
		SR240	556	602					130
		SR270	593	722					168
		AW13	510	640					115
		AW17	604	736					170
		AW17S	604		368	862			170
		AW20S	647		510	1200			240
	PN25/40 CL300	DA190	497	525			381	135	105
		DA210	522	532					125
		SR240	556	602					150
		SR270	593	722					188
		AW13	510	640					135
		AW17	604	736					190
		AW17S	604		368	862			190
		AW20S	647		510	1200			260
	PN63/110 CL600	DA190	530	525			508	165	125
		DA210	555	532					145
		SR240	589	602					170
		SR270	626	722					208
		AW17	637	736					210
		AW20	680	1020					280
		AW20S	680		510	1200			280
		AW28S	820		690	1578			525

注：本表尺寸和重量不包含附件。

# 浮动球阀外形尺寸



## 主要外形尺寸及重量

公称通径	压力等级	执行器	A	B	C	D	L	E	重量(Kg)
DN150 (6")	PN16 CL150	DA190	530	525			394	143	125
		DA210	555	532					145
		DA240	589	602					170
		SR240	589	602					170
		SR270	626	722					208
		AW13	543	640					155
		AW17	637	736					210
		AW20S	680		510	1200			280
	PN25/40 CL300	DA210	555	532			403	150	165
		DA240	589	602					190
		DA270	626	722					228
		SR240	589	602					190
		SR270	626	722					228
		SR300	648	742					240
AW17		637	736			230			
AW20		680	1020			300			
AW20S		680		510	1200	300			
AW25S		785		623	1435	490			
AW28S	820		690	1578	545				
DN200 (8")	PN16 CL150	DA240	689	602			457	170	250
		DA270	726	722					288
		SR270	726	722					288
		SR300	748	742					300
		AW17	737	736					290
		AW20	780	1020					360
		AW20S	780		510	1200			360
		AW28S	920		690	1578			605
	PN25/40 CL300	DA240	689	602			502	180	300
		DA270	726	722					338
		SR270	726	722					338
		SR300	748	742					350
		AW17	737	736					340
		AW20	780	1020					410
AW20S		780		510	1200	410			
AW25S		885		623	1435	600			
AW28S	920		690	1578	655				

注：本表尺寸和重量不包含附件。